

IN THE CLAIMS

Please amend the claims as follows:

1. (original) A camera module comprising a holder provided with a light-conducting channel, within which channel a lens having an optical axis is present, a solid-state image sensor being present near an end of said light-conducting channel, which image sensor comprises an image pick-up section oriented perpendicularly to the optical axis, characterized in that aligning means forming part of the holder are present near the end of the light-conducting channel, which aligning means align the image pick-up section with respect to the optical axis.

2. (original) A camera module as claimed in claim 1, characterized in that the image pick-up section extends in a plane parallel to a main surface of the solid-state image sensor, in which the solid-state image sensor comprises lateral surfaces oriented at least substantially perpendicularly to the main surface, and in which the holder comprises an outer wall which is at least substantially polygonal near the end, seen in sectional view in a direction perpendicular to the optical axis, in which the aligning means comprise bulges present on the outer wall, near the

corners of said polygon, which bulges extend beyond the end of the light-conducting channel, having an inner side which abuts against at least one of the lateral surfaces of the solid-state image sensor, as a result of which the solid-state image sensor is contained within the holder substantially without play in a direction perpendicular to the optical axis.

3. (original) A camera module as claimed in claim 2, characterized in that said polygon is a rectangle.

4. (currently amended) A camera module according to claim ~~2 or 3~~, characterized in that the inner side of the bulges comprises an L-shaped recess, as a result of which each bulge abuts substantially without play against two mutually adjacent lateral surfaces of the solid-state image sensor.

5. (original) A camera module as claimed in claim 4, characterized in that the recesses furthermore each comprise a surface extending parallel to a plane perpendicularly to the optical axis, which surfaces jointly form an abutting surface against which the main surface of the solid-state image sensor abuts substantially without play, thereby determining the distance from the image pick-up section to the lens.

6. (original) A camera module as claimed in claim 5, characterized in that further recesses are present in the holder near the end of the light-conducting channel, as a result of which the main surface of the solid-state image sensor does not make contact with the holder at the location of the recesses.

7. (original) A camera module as claimed in claim 2, characterized in that said bulges each have an end, which ends jointly form a bonding area which is oriented at least substantially perpendicularly to the optical axis.

8. (original) A camera module as claimed in claim 7, characterized in that the camera module comprises a substrate, in which the solid-state image sensor is provided with a second main surface bonded to the substrate, in which the substrate is bonded to the bonding area formed by the ends of the bulges by means of an adhesive material.

9. (original) A camera module as claimed in claim 2, characterized in that the main surface of the solid-state image sensor and the polygon are at least substantially identical in shape, with the polygon having a smaller surface area, as a result

of which a part of the main surface located near the lateral surfaces lies further away from the optical axis than, near the end of the light-conducting channel, the outer wall of the holder.

10. (original) A holder for use in a camera module, which holder is provided with a light-conducting channel, which is arranged for accommodating a lens having an optical axis and which is furthermore arranged for placing a solid-state image sensor comprising an image pick-up section near an end of the light-conducting channel, characterized in that aligning means forming part of the holder are present near said end of the light-conducting channel for aligning the image pick-up section with respect to the optical axis.

11. (original) A camera system comprising a camera module with a holder provided with a light-conducting channel in which a lens having an optical axis is present, in which a solid-state image sensor provided with an image pick-up section oriented perpendicularly to the optical axis is present near an end of the light-conducting channel, and in which aligning means forming part of the holder are present near said end of the light-conducting channel for aligning the image pick-up section with respect to the optical axis.

12. (original) A method of manufacturing a camera module comprising a holder, characterized in that the holder is provided with aligning means, in which the solid-state image sensor comes into contact with the aligning means upon placement of the solid-state image sensor in said holder, as a result of which an image pick-up section present on the solid-state image sensor is aligned with respect to an optical axis.